

FUCHTARDT



FMP 66-IV

Technical Specifications



FMP 66-IV

MOBILE READY TO RENT

*Photo is for reference only

FMP Mobile Series STANDARD FEATURES



Battery Isolator



E - Stop



DSE Controller



Fork Skid



Center Lift



ATS Connector




Outlets Kit



Fire Extinguisher



24 Hr tank



Bunded

FMP 66-IV Specs

Rated Power Prime (Kva)	60kVA
Rated Power Standby (Kva)	65kVA
Frequency (Hz)	50HZ
Rated Speed (RPM)	1500RPM
Rated Voltage (V)	415
PF (%)	0.8
Control System	Digital
Alternator Model	UCI 224E
Engine Model	NEF45SM1A
Dimensions (LxWxH mm)	3150 x 1243 x 1900
Wet Weight (Kg)	2478.0
Fuel Tank Capacity (L)	430


MOBILE READY TO RENT

As with stationary applications, a generator in a **mobile application** will be the main source of power, so fuel economy should be the primary decision-making criteria when selecting a generator. Mobile application generators are also moved from site to site using cranes, forklifts and trucks, and as such must be built with a very robust frame and canopy to ensure durability. Fuchardt's FMP Mobile series of generators come standard with a host of rental, construction and mining ready features, including bundled fork pocket skid base fuel tank, lockable battery isolators, centre lifts points, emergency stop, earth leakage protected outlet kits, fire extinguishers, and three way fuel valves for connection to external bulk fuel cells.

Engine Specs

Engine Make	NEF45SM1A
Manufacturer	IVECO
Cylinder Arrangement	Vertical inline
Number of Cylinders	4
Cycle	4 stroke
Aspiration	Turbocharged
Bore x Stroke (mm)	104 x132
Displacement (L)	4.5
Speed Governor	mech
Switchable	Y
Engine Gross Prime Power (kW)	53.3
Engine Gross Max. Power (kW)	58.8
Lube-oil Capability (L)	8.5
Fuel Consumption@75% load (L/h)	12.30
Starter Motor/ Charger Alternator (Vdc)	12 Vdc

Alternator Specs

Alternator Model	UCI 224E
Manufacturer	Stamford
Rated Output Power (kVA)	60.0
Alternator Type	Brushless
Phase	3
Poles	4
Exit Leads	12
IP Protection Class	IP 23
Insulation Grade	H
Winding Pitch	2/3
Bearing	single

MYNT PRODUCT RANGE:



GENERATORS 6KVA - 1500KVA




STANDBY




STATIONARY



MOBILE



TRAILER



CONTAINER



HEAVY DUTY




BIG TANK



WHISPER



WHISPER BIG TANK



INVERTER

FUEL CELLS 1KL - 100KL



LIFT & SHIFT




STATIC STORAGE



TOW TANKS




BULK STORAGE



SMARTS

DISTRIBUTION 10A - 1000A




HANDHELD




COMBO



STACKABLE



MASTER BOARD



LOAD BANKS

RENEWABLE RANGE




SOLAR GEN HYBRID



BATTERY




HYDROGEN



CONTAINER BATTERY

FILTER



FILTERS