




FT 22-PE Single

Technical Specifications



*Photo is for reference only

FT Standby and Stationary STANDARD FEATURES



Battery Isolator



Emergency Stop



DSE Controller



Fork Pocket
Skid



Center Lift



ATS Connector
Port



Outlets

FT 22-PE Single Specs

Rated Power Prime (Kva)	20kva
Rated Power Standby (Kva)	22kva
Frequency (Hz)	50HZ
Rated Speed (RPM)	1500RPM
Rated Voltage (V)	240
PF (%)	0.8
Control System	Digital
Alternator Model	TAL A42D-S
Engine Model	404D-22G L
Dimensions (LxWxH mm)	1950 x 993 x 1377
Wet Weight (Kg)	994
Fuel Tank Capacity (L)	80

STANDBY AND STATIONARY

A stationary application is where the generator is the main source of power, but it will spend all or most of its life in one location. Over 90% of the cost of operating a generator is fuel, so Fuchardt FT Stationary generators are fitted with fuel efficient, reliable European and Japanese Engines and STAMFORD Alternators.

A standby application is where mains power exists, and the generator is only operated in the event of blackout. The Fuchardt FT Standby Range is ready for plug and play installation. The units come with an Auto Mains Failure control system, soundproof canopy and fork skid base. Fuchardt FT Standby Generators also include a direct plug receptacle for an Automatic Transfer Switch. Out of the box, Fuchardt machines will detect a blackout, start automatically, transfer your load over to generator power, and then put your load back on mains and stop automatically once mains power is restored.

Engine Specs

Engine Make	404D-22G L
Manufacturer	PERKINS
Cylinder Arrangement	Vertical inline
Number of Cylinders	4
Cycle	4 stroke
Aspiration	Naturally aspirated
Bore x Stroke (mm)	84 x 100
Displacement (L)	2.2
Speed Governor	mech
Switchable	Y
Engine Gross Prime Power (kW)	18.4
Engine Gross Max. Power (kW)	20.3
Lube-oil Capability (L)	10.6
Fuel Consumption@75% load (L/h)	3.98
Starter Motor/ Charger Alternator (Vdc)	12 Vdc

Alternator Specs

Alternator Model	TAL A42D-S
Manufacturer	Leroy Somer
Rated Output Power (kVA)	21.3
Alternator Type	Brushless
Phase	1
Poles	4
Exit Leads	4
IP Protection Class	IP 23
Insulation Grade	H
Winding Pitch	2/3
Bearing	single


Other Products Available for sale and rental

purple
GlowBug



Hydrogen Light tower

purple
Skidibee



Stackable Solar

purple



Purple Pod



Purple Cube



Hydrogen

ASTON ELECTRIC



XL SERIES



XL AND WH



WHISPER

FUCHTARDT 



Lift & Shift



Static Storage



Containers

PIRATE
SMART-TANKS



Lift & Shift



Static Storage



Tow tanks

SUMO
PLUG N PLAY GEAR



Handheld Range



Midsize Distribution



Hardwire