

FUCHTARDT



FT 330-CU

Technical Specifications




FT 330-CU

STANDBY AND STATIONARY

*Photo is for reference only

FT Standby and Stationary STANDARD FEATURES



Battery Isolator



Emergency Stop



DSE Controller



Fork Pocket Skid



Center Lift



ATS Connector Port



Outlets

FT 330-CU Specs

Rated Power Prime (Kva)	300kVA
Rated Power Standby (Kva)	330kVA
Frequency (Hz)	50HZ
Rated Speed (RPM)	1500RPM
Rated Voltage (V)	415
PF (%)	0.8
Control System	Digital
Alternator Model	S4L1S-D4
Engine Model	6LTAA9.5-G1
Dimensions (LxWxH mm)	3800Å—1385Å—2100
Wet Weight (Kg)	3992
Fuel Tank Capacity (L)	470

STANDBY AND STATIONARY

A stationary application is where the generator is the main source of power, but it will spend all or most of its life in one location. Over 90% of the cost of operating a generator is fuel, so Fuchardt FT Stationary generators are fitted with fuel efficient, reliable European and Japanese Engines and STAMFORD Alternators.

A standby application is where mains power exists, and the generator is only operated in the event of blackout. The Fuchardt FT Standby Range is ready for plug and play installation. The units come with an Auto Mains Failure control system, soundproof canopy and fork skid base. Fuchardt FT Standby Generators also include a direct plug receptacle for an Automatic Transfer Switch. Out of the box, Fuchardt machines will detect a blackout, start automatically, transfer your load over to generator power, and then put your load back on mains and stop automatically once mains power is restored.

Engine Specs

Engine Make	6LTAA9.5-G1
Manufacturer	CUMMINS
Cylinder Arrangement	Vertical inline
Number of Cylinders	6
Cycle	4 stroke
Aspiration	Turbocharged
Bore x Stroke (mm)	116.5 x 148
Displacement (L)	9.5
Speed Governor	ECU
Switchable	Y
Engine Gross Prime Power (kW)	290
Engine Gross Max. Power (kW)	320
Lube-oil Capability (L)	32.4
Fuel Consumption@75% load (L/h)	52.5
Starter Motor/ Charger Alternator (Vdc)	24 Vdc

Alternator Specs

Alternator Model	S4L1S-D4
Manufacturer	Stamford
Rated Output Power (kVA)	300
Alternator Type	Brushless
Phase	3
Poles	4
Exit Leads	12
IP Protection Class	IP 23
Insulation Grade	H
Winding Pitch	2/3
Bearing	single


Other Products Available for sale and rental

purple
GlowBug



Hydrogen Light tower

purple
Skidibee



Stackable Solar

purple



Purple Pod



Purple Cube



Hydrogen

ASTON ELECTRIC



XL SERIES



XL AND WH



WHISPER

FUCHTARDT 



Lift & Shift



Static Storage



Containers

PIRATE SMART-TANKS



Lift & Shift



Static Storage



Tow tanks

SUMO PLUG N PLAY GEAR



Handheld Range



Midsize Distribution



Hardwire