


Static Storage: SS 12


CONTAINERISED , SELF BUNDED (DOUBLE WALL)



Containerised Fully Bunded (Double Wall)



Storage and Dispensing of Diesel, Lubricants, Kerosene, Petrol & Waste Oil



Culus Listed, tested to UL requirements



Smarter Fuel Cells

Unique rounded rectangular tank profile maximises the storage capacity of the tank and provides the strength of a cylindrical design. CSC plated as 10ft / 20ft / 40ft / 48ft Standard Container. Lockable Container Doors with option for Roller Door. Supplied with all required statutory safety decals for your region of operation.

Safer Fuel Cells


Integrated Bunded Pump Bay and Tank Access Platform design providing access to the full tank functionality in one convenient location on the tank. Vent that will relieve the gap between the two tanks in the event of a fire

Adaptable Fuel Cells


Full under tank visibility allows for regular visual inspect of the tank base and prevents the base rusting by providing for unrestricted air flow under the tank. 2 x 600mm manways with integrated tankaccess ladder assembly. Removable plate to allow the linking of multipl tanks in tank farm applications. Dispensing Equipment housed within a lockable bunded pump bay housing.

Specifications

Model	SS 12
Capacity	12,000L
Safe Fill Level	11,240L
Dimensions (mm)	3,000 x 2,438 x 2,896
Empty Weight (kg)	4500.0
Container Footprint	10FT High Cube
Integrated Pump Bay	Yes

Static Storage 8KL - 75 KL
Models


SS 8



SS 10




SS 12




SS 16



SS 30



SS 38



SS 65



SS 75

DN80

DN80 Fill Point c/w Camlock Male Fitting / Dust Cap / Fire Safe Full Bore Ball Valve / Wafer Style Non Return Valve.

DN80 Suction Outlet c/w Anti Syphon Valve and Two Piece Full Bore Fire Safe Ball Valve.

DN80 Mechanical Overfill Valve + 12V Battery

Operated Overfill Alarm.

Certifications

Certificate of Compliance #20120912-MH49221 for UL 142, ULC-S601

Paint

Paint Colour RAL9003 Signal White/ Tanks are sandblasted to SA2 Standard. Hempel Marine Paint 3 Stage process. Primer Hempadur 1530. 2nd Coat Hempadur HiBuild 4520. Final Coat Hempthane Enamel 55100 Finished dry



FUCHTARDT



ASTON ELECTRIC



PIRATE SMART-TANKS



SUMO
PLUG N PLAY GEAR

Product Family

GENERATORS 6KVA - 1500KVA



STANDBY



STATIONARY




MOBILE



TRAILER




CONTAINER



HEAVY DUTY



BIG TANK



WHISPER



WHISPER BIG TANK



INVERTER

FUEL CELLS 1KL - 100KL



LIFT & SHIFT



STATIC STORAGE



TOW TANKS



BULK STORAGE



SMARTS

DISTRIBUTION 10A - 1000A



HANDHELD



COMBO



STACKABLE



MASTER BOARD



LOAD BANKS