



# **Static Storage: SS 30**

# CONTAINERISED, SELF BUNDED (DOUBLE WALL)



Containerised Fully Bunded (Double Wall)



Storage and Dispensing of Diesel, Lubricants, Kerosene, Petrol & Waste Oil



Culus Listed, tested to UL requirements



#### **Smarter Fuel Cells**

# Unique rounded rectagular tank profile maximises the storage capacity of the tank and provides the strength of a cylindrical design. CSC plated as 10ft / 20ft / 40ft / 48ft Standard Container. Lockable Container Doors with option for Roller Door. Supplied with all required statutory safety decals for your region of operation.

#### **Safer Fuel Cells**

Integrated Bunded Pump Bay and Tank
Access Platform design providing access to the full tank functionality in one convenient location on the tank. Vent that will relieve the gap between the two tanks in the event of a fire

# **Adaptable Fuel Cells**

Full under tank visibility allows for regular visual inspect of the tank base and prevents the base rusting by providing for unrestricted air flow under the tank. 2 x 600mm manways with integrated tankaccess ladder assembly. Removable plate to allow the linking of multipl tanks in tank farm applications. Dispensing Equipment housed within a lockable bunded pump bay housing.

## **Specifications**

Model	SS 30
Capacity	30,000L
Safe Fill Level	29,350L
Dimensions (mm)	6,058 x 2,438 x 2,896
Empty Weight (kg)	7500.0
Container Footprint	20FT High Cube
Integrated Pump Bay	Yes



# **1300 415 240** myntgroup.com.au

# Static Storage 8KL - 75 KL

Models



#### **DN80**

DN80 Fill Point c/w Camlock Male Fitting /
Dust Cap / Fire Safe Full Bore Ball Valve /
Wafer Style Non Return Valve.
DN80 Suction Outlet c/w Anti Syphon
Valve and Two Piece Full Bore Fire Safe
Ball Valve.
DN80 Mashanisal Overfill Valve + 12/4

DN80 Mechanical Overfill Valve + 12V Battery

Operated Overfill Alarm.

### Certifications

Certificate of Compliance #20120912-MH49221 for UL 142, ULC-S601

#### **Paint**

Paint Colour RAL9003 Signal White/ Tanks are sandblasted to SA2 Standard. Hempel Marine Paint 3 Stage process. Primer Hempadur 1530. 2nd Coat Hempadur HiBuild 4520. Final Coat Hempathane Enamel 55100 Finished dry



























# **Product Family**

# **GENERATORS 6KVA - 1500KVA**











**MOBILE** 

**TRAILER** 

**CONTAINER** 









**WHISPER** 





**INVERTER** 

# **FUEL CELLS 1KL - 100KL**







STATIC STORAGE



**TOW TANKS** 



**BULK STORAGE** 



**SMARTS** 

# **DISTRIBUTION 10A - 1000A**



**HANDHELD** 



**COMBO** 



**STACKABLE** 



**MASTER BOARD** 



**LOAD BANKS**